

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/17/2008

Reviewed on 01/17/2008

**1 Identification of substance**

MSDS #TS12A

**Trade name:** FASTLANE AEROSOL WHITE

**MANUFACTURED FOR:**  
**PIONEER MANUFACTURING CO**  
 4529 INDUSTRIAL PKWY  
 CLEVELAND, OH 44135  
 PHONE NUMBER: 800-877-1500

**Phone Numbers:**  
**Information: 800-321-1976**  
**Emergency: 800-535-5053**

**2 Composition/Data on components****Chemical Description:** This product is a mixture of the substances listed below with nonhazardous additions.**Dangerous components:**

64742-89-8	VM&P Naptha	25.96%
74-98-6	propane	12.6%
13463-67-7	titanium dioxide	8.36%
106-97-8	n-butane	7.4%
7727-43-7	barium sulphate, natural	5.83%
1317-65-3	Calcium Carbonate	5.1%
64742-47-8	Mineral Spirits	3.12%

**Additional information:** For the wording of the listed risk phrases refer to section 3.**3 Hazards identification****Effects of short-term overexposure:**

Vapors cause irritation to the eyes, nose, throat, skin, and central nervous system. Symptoms may include dizziness, throat irritation, headache, fatigue, swelling of eyes, and nausea.

**Effects of chronic overexposure:**

May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be harmful or fatal.

**NFPA ratings (scale 0 - 4):** Health- 1  
 Flammability- 3  
 Reactivity- 3

**HMIS-ratings (scale 0 - 4):** Health- 1  
 Flammability- 3  
 Physical Hazard-3

**4 First aid measures****After inhalation:**

Supply fresh air; consult doctor in case of complaints.

**After skin contact:**

Remove contaminated clothing. Wash exposed area with soap and water.

**After eye contact:**

Move to fresh air. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

**After swallowing:**

Contact physician or poison control center.

**5 Fire fighting measures****Extinguishing agents:**

CO2, sand, extinguishing powder, or water spray. Fight larger fires with water spray or alcohol resistant foam.

**Protective equipment:**

No special measures required.

**6 Accidental release measures****Safety precautions:**

Wear protective equipment. Keep unprotected persons away.

**Environmental precautions:**

Inform appropriate authorities in case of seepage into water course or sewage system.  
 Do not allow product to reach sewage systems or ground water.

**Cleanup/Collection:**

Do not flush with water or aqueous cleansing agents. Use diluted caustic solution. Soak up spills with inert absorbent material. Refer to section 13 for disposal information.

**7 Handling and storage****Fire/explosion protection:**

Do not spray on a naked flame or any incandescent material.  
 Do not smoke. Protect from electrostatic charges.

(Contd. on page 2)

USA

**FOR CHEMICAL EMERGENCY****Call INFOTRAC****1-800-535-5053****24 Hrs. per day, 7 days per week**

**WARNING:** This product contains a chemical known to the State of California to cause cancer.

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/17/2008

Reviewed on 01/17/2008

Trade name FASTLANE AEROSOL WHITE

MSDS #TS12A

**Storage requirements:** Observe pressurized container storage regulations. Consult with your local authorities.  
Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

(Contd. of page 1)

## 8 Exposure controls and personal protection:

### Components with limit values that require monitoring at the workplace:

#### 74-98-6 propane

PEL 18000 mg/m<sup>3</sup>, 1000 ppmREL 1800 mg/m<sup>3</sup>, 1000 ppmTLV Varies mg/m<sup>3</sup>, 1000 ppm

#### 106-97-8 n-butane

REL 1900 mg/m<sup>3</sup>, 800 ppmTLV Varies mg/m<sup>3</sup>, 1000 ppm

#### 7727-43-7 barium sulphate, natural

PEL 15\* 5\*\* mg/m<sup>3</sup>

\*total dust \*\*respirable fraction

REL 10\* 5\*\* mg/m<sup>3</sup>

\*total dust \*\*respirable fraction

TLV 10 mg/m<sup>3</sup>

E

**Hygienic measures:** Keep away from foodstuffs and animal feed. Wash hands after use.

**Breathing equipment:** Use suitable respiratory protective device in case of insufficient ventilation.

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases of inadequate ventilation, a respiratory protective device should be worn to prevent overexposure.

**Protection of hands:** Protective gloves. The glove material has to be impermeable and resistant to the substance. No glove recommendation can be given.

**Eye protection:** Tightly sealed goggles

## 9 Physical and chemical properties:

### General Information:

Form: Aerosol

Color: According to trade name description in section 1.

Odor: Solvent

Boiling point/Boiling range: -44°C (-47°F)

Flash point: -19°C (-2°F)

Ignition temperature: 365°C (689°F)

Auto igniting: Product is not self-igniting.

**Danger of explosion:** Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120 degrees fahrenheit.

In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 0.9 Vol %

Upper Explosion Limit: 10.9 Vol %

Vapor Pressure: ~40 PSI, 2750 hPa

Density at 20°C (68°F): 0.89 g/cm<sup>3</sup>

Specific Gravity: Between 0.77 and 0.85 (Water equals 1.00)

VOC content: 540.4 g/l / 4.51 lb/gal

VOC content (less exempt solvents): 50.9 %

Water: 18.1 %

MIR Value: 0.67

Solids content: 30.4 %

## 10 Stability and reactivity:

**Conditions to be avoided:** Do not allow the can to exceed 120 degrees Fahrenheit. Stable at normal temperatures.

**Hazardous Reactions:** No dangerous reactions known.

## 11 Toxicological information:

**Primary effect on the skin:** No irritant effect.

**Primary effect on the eye:** Irritating effect.

(Contd. on page 3)

USA

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/17/2008

Reviewed on 01/17/2008

**Trade name:** FASTLAND AEROSOL WHITE

MSDS # TS12A

(Contd. of page 2)

**Sensitization:** No sensitizing effects known.  
**Other information:** Harmful

**12 Ecological information**

**Other information:** This product does not contain any chloroflourocarbons (CFC's), chlorinated solvents, lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyl (PBB), or polybrominated diphenyl ether (PDBE). No specific ecological data is available for this product.

**Acquatic toxicity:** Hazardous for water, do not empty into drains.

**13 Disposal considerations**

**DISPOSAL METHOD:** Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

**Recommendation:** Empty cans should be recycled.

**14 Transport information:**

**Hazard class:** 2.1  
**Identification number:** N/A  
**Label:** 2.1  
**ADR/RID class:** 2 5F Gases  
**UN-Number:** 1950  
**IMDG Class:** 2.1  
**Packaging group:** II  
**EMS Number:** F-D,S-U  
**Marine pollutant:** No  
**ICAO/IATA Class:** 2.1  
**Proper shipping name:** Aerosols, Flammable  
 Consumer Commodity ORM-D

**15 Regulations****SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

**SARA Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

**TSCA (Toxic Substances****Control Act):** All ingredients are listed.**PROPOSITION 65 Chemicals known to cause cancer:**

100-41-4 | ethyl benzene

**Canadian WHMIS:** Class A, B5---Flammable Aerosols**EPA:**

A= Known human carcinogen      B= Probable human carcinogen

C= Possible human carcinogen

D= Not classifiable as to human carcinogenicity: Inadequate human and animal evidence of carcinogenicity (or no data is available).

**IARC:** Group 2B: The ingredient is possibly carcinogenic to humans. There is limited evidence of carcinogenicity.  
 Group 3: The ingredient is unclassifiable as to its carcinogenicity to humans.

13463-67-7 | titanium dioxide

2B

**ACGIH TLVs:**

A1-designates a confirmed human carcinogen.

A2-designates a suspected human carcinogen.

A3-designates an animal carcinogen.

A4-designates "not classifiable as a human carcinogen".

13463-67-7 | titanium dioxide

A4

**NIOSH:**

13463-67-7 | titanium dioxide

**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Contact:** Regulatory Affairs